

ESS-200kW/372kWh
 ESS-200kW/417kWh
 工商业储能
 液冷一体机

昆宇电源
 COSPOWERS



灵活扩容，一机多效
 匹配多种应用场景



多重
 保护系统



高集成化设计
 交直流一体



指尖监控
 云端维护

| 参数 / 型号 | | 200 kW / 372 kWh | 200 kW / 417 kWh |
|---------|-----------|-----------------------|----------------------|
| 直流侧参数 | 直流路数 | 1路 | 1路 |
| | 直流母线最高电压 | 1500V | 1500V |
| | 直流侧最大电流 | 189A | 189A |
| | 直流电压工作范围 | 1060-1500V | 1060-1500V |
| 交流侧参数 | 最大输入视在功率 | 220kVA | 220kVA |
| | 最大输入有功功率 | 200kW | 200kW |
| | 额定输入电压 | 690A | 690A |
| | 最大持续输入电流 | 184A | 184A |
| | 额定输入频率 | 50/60Hz | 50/60Hz |
| 电池参数 | 电池类型 | 磷酸铁锂 | 磷酸铁锂 |
| | 额定电量 | 372KWh | 417kWh |
| | 标称电压 | 1331.2V | 1331.2V |
| | 工作电压范围 | 1164.8V-1456V | 1164.8V-1456V |
| | 倍率 | ≤0.5C | ≤0.5C |
| 系统参数 | 人机界面 | 8寸 LCD触摸屏 | 8寸 LCD触摸屏 |
| | 消防系统 | 全氟己酮消防 | 全氟己酮消防 |
| | 冷却方式 | 液冷 | 液冷 |
| | 工作温度 | 0~55°C | 0~55°C |
| | 防护等级 | IP54 | IP54 |
| | 尺寸(W*D*H) | <1400mm*1400mm*2350mm | 1400mm*1400mm*2350mm |
| | 重量 | <3500Kg | <3600Kg |



昆宇电源股份有限公司

网址:WWW.COSPOWERS.COM

地址:山东省东营市东营区东七路28号

电话:0546-7768891

版权及最终解释权归昆宇电源股份有限公司所有

ESS-200kW/372kWh

ESS-200kW/417kWh

LIQUID-COOLING LITHIUM
BATTER ENERGY STORAGE
SYSTEM CABINET



flexible expansion, one machine
multi-effect matching a variety
of application scenarios



Multiple Protection
Systems



highly integrated
design AC and DC
integrated



fingertip monitoring
cloud maintenance

| Parameters/ Model | | 200kW/372kWh | 200kW/417kWh |
|--------------------------|----------------------------------|--------------------------------|--------------------------------|
| DC side basic parameters | DC branch | 1 channel | 1 channel |
| | DC busbar maximum voltage | 1500V | 1500V |
| | DC side maximum current | 189A | 189A |
| | DC voltage operating range | 1060-1500V | 1060-1500V |
| AC side basic parameters | Maximum input apparent power | 220kVA | 220kVA |
| | Maximum input active power | 200kW | 200kW |
| | Rated input voltage | 690A | 690A |
| | Maximum continuous input current | 184A | 184A |
| | Rated input frequency | 50/60Hz | 50/60Hz |
| Battery parameters | Battery Type | LFP | LFP |
| | Rated capacity | 372KWh | 417kWh |
| | Nominal voltage | 1331.2V | 1331.2V |
| | Operating voltage range | 1164.8V-1456V | 1164.8V-1456V |
| | Charge/Discharge Rate | ≤0.5C | ≤0.5C |
| System parameters | HMI | 8 inch LCD touch screen | 8 inch LCD touch screen |
| | Fire protection system | Perfluorhexone fire protection | Perfluorhexone fire protection |
| | Cooling Method | Liquid cooling | Liquid cooling |
| | Operating temperature | 0~55°C | 0~55°C |
| | IP Class | IP54 | IP54 |
| | Size (W*D*H) | <1400mm*1400mm*2350mm | 1400mm*1400mm*2350mm |
| | Weight | <3500Kg | <3600Kg |



Cospowers Technology Co., Ltd.

W:WWW.COSPOWERS.COM

A:No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T:+86-546-7768891

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.