

PowerCrate-CE-5

低压壁挂式储能电池

昆宇电源
COSPOWERS



- 1 外观设计极其简洁，外观优雅，防护等级为IP40
- 2 支持多个电池模块并联，最多可达8个模块
- 3 安装和维护方便，可定制设计以满足不同客户的需求
- 4 具有多重保护和报警系统，安全可靠

参数/型号		CE-5
电池参数	额定电压	51.2V
	电压范围	45~57.6V
	电量	5120Wh
	最大充放电电流	1C
	电池类型	LFP
工作条件	工作温度范围	0~45℃
	存储温度范围	-15~60℃
	湿度	5~95%
	冷却方式	自然冷却
	重量	53Kg
	尺寸 (W*D*H)	430*186*600mm
	安装方式	壁挂式
	通讯方式	CAN/RS485
其他参数	匹配逆变器	派能、古瑞瓦特、硕日、固德威、锦浪、鹏城、日月源、Victron、索瑞德、施耐德、SMA、美世乐、拓宝、STUDER
	认证	IEC62619、CE-EMC、FCC、UL1973、UL9540A



深圳昆宇电源科技有限公司
网址:WWW.COSPOWERS.COM
地址:深圳市宝安区燕罗街道罗田社区第三工业区广田路2号
电话:0755-33185898
版权及最终解释权归深圳昆宇电源科技有限公司所有

Low-voltage wall-mounted energy storage battery



- 1

Extremely simple design in appearance, elegant appearance, IP40
- 2

It supports multiple battery modules in parallel, up to 8 modules
- 3

Multiple protection and alarm system, safe and reliable
- 4

Easy installation and maintenance, customized design to meet the requirements of different customers

Parameters/ Model		CE-5
Battery Parameters	Rated Voltage	51.2V
	Voltage Range	45~57.6V
	Battery Capacity	5120Wh
	Maximum Charge/Discharge Current	1C
	Battery Type	LFP
Operating Conditions	Operating Temperature Range	0~45℃
	Storage Temperature Range	-15~60℃
	Humidity	5~95%
	Cooling Method	Natural Cooling
	Weight	53Kg
	Dimensions (W*D*H)	430*186*600mm
	Installation Method	Wall-Mounted
	Communication Interface	CAN/RS485
Other Parameters	Compatible Inverter	Pylontech, Growatt, Solis, Goodwe, Ginlong, Prowatt, Sinoyaz, Victron, SuoRuid,Schneider, SMA, Maruson, Topbatt, STUDER
	Certifications	IEC62619、CE-EMC、FCC、UL1973、UL9540A

